



GTIN: 7640455521328

- Hager IP55 control box, white, for operating a Casambi system without app
- 6 buttons with LED
- Cable gland M20
- Built-in LIGA.AIR.8T.8LED 110-240 VAC
- Easy commissioning via Casambi

Installation by a qualified electrician in accordance with local regulations!

Technical data:

Dimensions (D x W x H) / weight	87 x 87 x 82 mm, W: 320 g
Colours	Housing size 1 white
Mounting	Surface-mounted
Ambient conditions, housing temperature Tc	Operation: temperature -20 ... 50 °C, humidity < 85 %rH Storage, transport: temperature -25 ... 65 °C, humidity < 95 %rH, Tc: 70 °C
Protection rating / protection class	IP55 per EN 60529 / protection class II
Supply connections	Brown (BN): L line, Blue (BL): N neutral
Power consumption	0.7 W
Standards	Low Voltage Directive 2014/35/EU per EN 60669-2-1, EMC Directive 2014/30/EU
CASAMBI module standards	Bluetooth Wireless Control
Programming	With Casambi app (App Store, Google Play)
Applications	Control of CASAMBI scenes, luminaires, blinds, relays, etc.
Scope of delivery	Ready to operate, enclosure with 6 buttons, 6 LEDs and connection terminals

Function description

Casambi APP operation / action	Function
6 buttons with LED	Switch to OFF / pressed scene indicated by LED

Compatible devices:

Range:



Casambi uses Mesh network technology. Each device acts as a repeater and refreshes the received Bluetooth signal for the following devices.

Greater ranges can be achieved with additional Casambi devices.

The range also depends heavily on the surroundings and on obstacles such as walls and building materials.

